

SERIAL NO. 10/761,828

PATENT
PD030017

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Hui Li, et al.
Serial No.: 10/761,828
Filed: January 20, 2004
For: Device and Method for Generating Metadata From Essence

CLAIM OF PRIORITY UNDER 35 USC 119

Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

Sir:


Applicants hereby claim the benefit of priority under 35 USC 119 and under the International Convention for the Protection of Industrial Property, of European Application No. 03001175.3, filed January 21, 2003.

A certified copy of the priority document is enclosed.

Respectfully submitted,

Hui Li, et al.

By


Joel M. Fogelson
Reg. No. 43,613
(609) 734-6809

Thomson Licensing Inc.
Patent Operations
P.O. Box 5312
Princeton, NJ 08543-5312

April 19, 2004

Certificate of Mailing Under 37 C.F.R. 1.8

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Commissioner for Patents, Alexandria, Virginia 22313-1450 on:

April 19, 2004
Date

Dorothy Kerrick
Dorothy Kerrick



1

2

3

4

5

6

7



**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03001175.3

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk



Anmeldung Nr:
Application no.: 03001175.3
Demande no:

Anmeldetag:
Date of filing: 21.01.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

DEUTSCHE THOMSON-BRANDT GMBH
Hermann-Schwer-Strasse 3
78048 Villingen-Schwenningen
ALLEMAGNE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se referer à la description.)

Device and method for generating metadata from essence

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

H04N/

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL PT SE SI SK

PD030017*Ri*20.01.2003.

1

Device and method for generating metadata from essence

The present invention relates to a method for processing
5 multimedia data including the step of providing at least one
selected essence data, wherein essence data represents in-
formation being directly perceptible by a user. Furthermore,
the present invention relates to a corresponding device for
processing multimedia data.

10

Background

Multimedia data may include metadata being data about data.
Metadata is a special kind of data, which is linked to other
15 data called essence. Metadata is typically used as index
message for essence. Essence is the basic data, such as text
essence, picture essence, video essence, or audio essence.

The metadata structure is essentially characterized by two
20 parts: metadata-essence (MD-essence) and metadata-link (MD-
link). MD-essence is part of a metadata, which is designed
to be human-perceptible, and which serves as the proxy by
which the metadata will be presented to the user in any user
interface of systems employing metadata. MD-link is part of
25 the metadata, which links to any kind of essence.

A way how to generate efficient metadata is always an impor-
tant issue for metadata applications. A possible way for ge-
nerating metadata is to convert essence into metadata. In
30 practice, some essence, such as text essence or thumbnail
picture essence, contains a lot of compact information which
can be utilized for metadata. Usually, content of essence
can be converted directly into metadata essence. However, it
is a problem to generate MD-link data conveniently in case
35 of conversion of essence into metadata.

PD030017*Ri*20.01.2003

2

Invention

In view of that it is the object of the present invention to provide a device and a method for conveniently generating
5 MD-link data, while generating metadata from essence..

According to the present invention this object is solved by a method for processing multimedia data including the steps of providing at least one selected essence data, wherein es-
10 sence data represents information being directly perceptible by a user, providing a metadata template to be used to form at least a first metadata, providing a list of links to a plurality of second essence data and/or a list of a plural-
15 ity of second metadata and forming said at least first metadata on the basis of said at least one selected essence data and said list of links and/or said list of second metadata by applying said metadata template.

Furthermore, according to the present invention there is
20 provided a device for processing multimedia data including first storing means for providing at least one selected essence data, wherein essence data represents information being directly perceptible by a user, second storing means for providing a metadata-template to be used to form at least a
25 first metadata, third storing means for providing a list of links to a plurality of second essence data and/or a list of a plurality of second metadata and processing means connected to that first, second and third storing means for forming said at least first metadata on the basis of said at
30 least one selected essence data and said list of links and/or said list of second metadata by applying said metadata-template.

Accordingly, there is provided a basic method and device for
35 conversion of essence into metadata for users with pre-knowledge for generating MD-links. Additionally, there may be provided an advanced method for conversion of essence

PD030017*R1*20.01.2003

3

into metadata based on a relationship-chain between essence and metadata, wherein the user may be without any pre-knowledge for generating MD-links efficiently. In other words, the user is given an intelligent metadata editing method or an assistant tool for metadata editing.

Preferably, second metadata linked with the at least one selected essence data is used for forming the first metadata. This is an essential help for the user to edit the first metadata. He does not have to look through the whole list of current metadata to find content-related further information. Instead of this, the user obtains a valuable hint to closely content correlated essence from the second metadata. Thus he does not have to go through the whole list of current metadata but highly relevant essence data are proposed automatically.

The at least first metadata may be formed by taking over the at least one selected essence into a MD-essence space of the metadata-template. This means, that the essence data or part of essence data are simply transferred to the metadata-template without any transformation.

The at least first metadata is advantageously formed by adding one or more MD-links of the second metadata into a MD-link space of the metadata-template. This means, that the MD-links are simply formed by transferring the MD-links from other metadata into the new metadata without transformation.

Third metadata and/or third essence data linked with MD-links of the second metadata may be used for forming the MD-essence and/or metadata-links of the first metadata. Therefore, a relation-chain of links having any length may be used to automatically propose a convenient metadata.

Fortunately, a forming or editing process of the metadata is performed with the help of a graphic user interface (GUI).

PD030017*Ri*20.01.2003

4

Such a GUI represents a comfortable assistance tool for editing metadata.

The present invention will now be described in more detail in connection with the attached drawings, showing in:

Figure 1 a schedule for converting essence into metadata according to a basic method of the present invention; and

10

Figure 2 a schedule for converting essence into metadata according to an advanced method of the present invention.

15 Exemplary embodiments

For conversion of essence into metadata, essence data can be directly converted into MD-essence. The problem is how to conveniently generate a meaningful MD-link for it. To solve this problem, a basic and an advanced method are described in the following, which utilize the relationship between existing essence and metadata to generate a significant MD-link.

25 A basic method, which converts an essence into metadata and utilizes other existing essence or metadata to set up metadata references is composed as following:

I. Basic method:

30

a) As shown in Fig. 1, the task of this basic method is to combine a selected essence 1 with a provided metadata template 2. The metadata template 2 includes a MD-essence 3 and MD-link(s) 4.

35

b) As further shown in Fig. 1, a graphic user interface (GUI) 5 can browse or operate the following components:

the selected essence 1, the metadata template 2, a list of links to existing essences 6 and a list of current existing metadata 7.

- 5 c) Using a GUI 5 operation, the user may convert the selected essence 1 into metadata 2 through taking over essence 1 into MD-essence 3. The essence 1 can be a text, a picture (such as a thumbnail picture), an audio or a video-clip. If the MD-essence 3 contains a picture, an
10 audio or a video clip, the metadata 2 is a kind of rich metadata.
- d) After converting essence 1 into MD-essence 3, it still
15 needs to generate the MD-link(s). Without MD-link(s) information, metadata are meaningless. In this basic method, the user may browse a list of links to existing essences 6 and a list of existing metadata 7 with the GUI 5. The user may select desired links to the present essence from the list of links to essence 6 and add the selected links to MD-link 4. Furthermore, the user may select
20 metadata from the metadata list 7 and generate a link information to the selected metadata, and add the generated link to MD-link 4.
- 25 e) After above editing process, a new metadata is generated, which is based on the metadata template 2. Its MD-essence 3 is taken over from selected essence 1 and its MD-link(s) 4 is generated from list of links of existing essence 6 and metadata 7.

30

According to this basic method, a selected essence 1 is converted into a new metadata 2, wherein the user has to do most of the work of finding or generating the new MD-link(s) 4. The user must generate a metadata link according to his
35 own pre-knowledge or understanding. He sets up MD-link 4 through selecting and generating a link message from

PD030017*Ri*20.01.2003

6

existing essence and metadata. In this procedure, the user cannot use any assistant information to simplify his selection and judgment process. However, in a lot of cases it is difficult to generate efficient and correct MD-link by only using above basic method. Therefore, an advanced method is proposed here, which can make use of associated reference information to help the user to select efficient and significant MD-link(s) for the new metadata:

II. Advanced method:

a) As shown in Fig. 2, the advanced method includes all functions and components of the basic method as described above in I.(a)-(e).

b) As alternative way to the basic method, in the advanced method, the user may search in a metadata database for all metadata 8, which are linked to the selected essence 1. The metadata 8 have their own MD-essences 9 and MD-links 10. Each MD-link 10 directs to essence 1.

c) The metadata 8 can be viewed and operated by GUI 5.

d) The MD-essence 9 of metadata 8 can be used as additional reference material for editing MD-essence 3 of metadata 2. For example, the user may take the MD-essence 9 to improve MD-essence 3.

e) The metadata 8 provides useful hints for users. Based on metadata 8, the user may generate improved reference link data for the new generated metadata 2. For example, besides MD-link 10, the metadata 8 may include an other MD-link 11, which links to another metadata or essence 12. Within metadata 8 all MD-links 10, 11 are content-associated. Therefore, metadata/essence 12 and essence 1 are closely content-related entities. Thus, metadata/essence 12 is a good reference candidate for the new

PD030017*Ri*20.01.2003

7

metadata 2. In this case, metadata 2 should have a reference link, which directs to the metadata/essence 12. If the user decides to take over the MD-link(s) 11 as reference link into metadata 2, he can simply add the MD-link(s) 11 to MD-link(s) of metadata 2.

f) Further, the user may make use of the hint of metadata 8 to find further content-related entities of essence 1, or reference link data of metadata 2. For example, the user may look for interested reference information in metadata/essence 12 and generate MD-link to metadata 2. Thereby the user may find other associated metadata/essence 13 and generate a possible MD-link for metadata 2 on the basis of metadata/essence 13.

g) The user completes all above steps under GUI 5 operation.

In Fig. 2. entities 1, 8, 12, 13 ... form of a kind of relationship-hint-chain. This relationship-hint-chain makes it possible to let the user easily find out associated reference links for the new metadata 2. This is a fast way to get desired entities from hundreds and thousands of candidates.

The basic method and the advanced method for converting essence into metadata may be employed in parallel. If the user has enough pre-knowledge for generating reference link data, the user may use the basic method described above in (I), otherwise, the user may use the advanced method described in (II) and based on the relationship-hint-chain to generate a significant metadata link.

For better understanding of the above methods the following application examples are given:

1. A user will generate a new metadata based on an existing photo (essence 1). The content of the selected photo is about Eiffel tower in Paris. At first, the user will con-

PD030017*Ri*20.01.2003

8

vert the photo into MD-essence 3. If the original photo has a big format, the new generated MD-essence photo can be converted into a shrunk formatted picture, such as a thumbnail photo. Now the user has a metadata with a MD-essence part. Second, the user must set up significant reference links for this metadata according to one of the two methods:

- a) Based on the above described basic method, the user may browse lists of all existing essences or metadata and manually generate MD-links to preferred essences or metadata, such as a film about the Eiffel tower, a biographical article about the designer of the Eiffel tower, a metadata which includes many useful reference links about the Eiffel tower and Paris, etc. The problem for this method is that if there are a lot of possible candidate essences or metadata, it is difficult for the user to generate reference links correctly and quickly.
- b) Based on the above described advanced method, the user does not need to browse all essences or metadata. The user only has to check existing metadata 8 which link to the selected Eiffel tower photo (essence 1). If there exists any metadata 8 which points to the selected photo, the user may simply check all reference links 11 of the metadata 8. The user may look for preferred entities following these reference links 11 and select interested references and set up MD-links 4 for the new created metadata 2. When using the advanced method, the user may set up the same MD-link 4 as the above basic method, such as links to some films, pictures or articles about Eiffel tower and Paris. However, the advanced method is more efficient and faster in case of larger essence and metadata databases.

2. A user will generate a new metadata based on a movie (essence 1) - "The Lost World (Jurassic Park II)". The user

As can be seen from the above examples, both methods provide a comfortable assistant tool for metadata editing.

PD030017*Ri*20.01.2003

10

Claims

1. Method for processing multimedia data including the
5 steps of
- providing at least one selected essence data (1),
wherein essence data represents information being di-
rectly perceptible by a user,
- 10 characterized by
- providing a metadata template (2) to be used to form at
least a first metadata,
- 15 providing a list of links (6) to a plurality of second
essence data and/or a list of a plurality of second meta
data (7) and
- 20 forming said at least first metadata on the basis of
said at least one selected essence data (1) and said
list of links (6) and/or said list of second metadata
(7) by applying said metadata template (2).
- 25 2. Method according to claim 1, wherein second metadata
linked with said at least one selected essence data (1)
is used for forming said first metadata.
3. Method according to claim 1 or 2, wherein said at least
30 first metadata is formed by taking over said at least
one selected essence data (1) into a MD-essence space
(3) of said metadata template (2).
4. Method according to one of the claims 1 to 3, wherein
35 said at least first metadata is formed by adding one or
more MD-links of said second metadata (8) into a MD-link

PD030017*Ri*20.01.2003

11

space (3) of said metadata-template (2).

5. Method according to one of the claims 1 to 4, wherein
third metadata and/or third essence data (12, 13) linked
5 with MD-links (10, 11) of said second metadata (8) are
used for forming said MD-essence and/or MD-links of said
first metadata.

6. Method according to one of the claims 1 to 5, wherein
10 the step of forming said at least first metadata is per-
formed by a graphic user interface (5).

7. Device for processing multimedia data including first
storing means for providing at least one selected es-
15 sence data (1), wherein essence data represents informa-
tion being directly perceptible by a user,

characterized by

20 second storing means for providing a metadata-template
(2) to be used to form at least a first metadata,

third storing means for providing a list of links (6) to
a plurality of second essence data and/or a list of a
25 plurality of second metadata (7) and

processing means connected to said first, second and
third storing means for forming said at least first
metadata on the basis of said at least one selected es-
30 sence data (1) and said list of links (6) and/or said
list of second metadata (7) by applying said metadata-
template (2).

8. Device according to claim 7, which is connectable to
35 fourth storing means or storing second metadata (8)
linked with said at least one selected essence data (1),
wherein said second metadata (8) are usable for forming

said first metadata.

- 5 9. Device according to claim 7 or 8, wherein said at least first metadata is formable by taking over said at least one selected essence data (1) into a metadata essence space (3) of said metadata-template (2) by said processing means.
- 10 10. Device according to one of the claims 7 to 9, wherein said at least first metadata is formable by adding one or more MD-links (10, 11) of said second metadata (8) into a MD-link space (4) of that metadata-template (2) by said processing means.
- 15 11. Device according to one of the claims 7 to 10, which includes fifth storing means connected to said processing means for storing third metadata and/or third essence data (12, 13) linked with MD-links (11) of said second metadata (8), wherein said third metadata and/or said
20 third essence data (12, 13) are usable for forming said MD-essence and/or said MD-links of said first metadata.
- 25 12. Device according to one of the claims 7 to 10, further including a graphic user interface (5) connected to said processing means for forming said at least first metadata.

PD030017*Ri*20.01.2003

13

Abstract**Device and method for generating metadata from essence**

- 5 The generation of metadata shall be simplified. Therefore, a method is presented in which a metadata-template (2) is filled with selected essence (1) and MD-links obtained from a list of links to essence (6) and/or a list of current metadata (7). Furthermore, it is possible to obtain the MD-
- 10 links from further metadata or essences (8, 12, 13) directly or indirectly linked with the selected essence (1).

(Fig. 2)

PD030017

1/2




Fig. 1

PD030017

2/2




Fig. 2

